

# Energiedaten

## energy information

Programm Programme	Artikel article	TEIBEZ	EEK EEC	Leistung in [W] Power in [w]	Farbtemperatur in Kelvin color tempera- ture in kelvin	Lichtleistung in Lumen [lm] light output in lumen [lm]
<b>OPTIbasic</b>						
4010	SAB60	LED-Aufbauleuchte Chrom 300 mm	A–A++	1,9	6000	130
4010	SAB80	LED-Aufbauleuchte Chrom 300 mm	A–A++	1,9	6000	130
4010	SAC60	Profil incl. LED	A–A++	5,3	6500	352
4010	SAC80	Profil incl. LED	A–A++	7,2	6500	480
4010	SBA60	FLEX LED SET	A–A++	5,3	6250–6750	352
4010	SBA80	FLEX LED SET	A–A++	7,2	6250–6750	480
4020	SAB60	LED-Aufbauleuchte Chrom 300 mm	A–A++	1,9	6000	130
4020	SAB80	LED-Aufbauleuchte Chrom 300 mm	A–A++	1,9	6000	130
4020	SAC60	Profil incl. LED	A–A++	5,3	6500	352
4020	SAC80	Profil incl. LED	A–A++	7,2	6500	480
4020	SBA60	FLEX LED SET	A–A++	5,3	6250–6750	352
4020	SBA80	FLEX LED SET	A–A++	7,2	6250–6750	480
4030	SAB60	LED-Aufbauleuchte Chrom 300 mm	A–A++	1,9	6000	130
4030	SAB80	LED-Aufbauleuchte Chrom 300 mm	A–A++	1,9	6000	130
4030	SBA60	FLEX LED SET	A–A++	5,3	6250–6750	352
4030	SBA80	FLEX LED SET	A–A++	7,2	6250–6750	480
4040	SOB60	LED-Strahler, 2x	A+	2 x 1,5	4000	2x95
4040	SOB80	LED-Strahler, 2x	A+	2 x 1,5	4000	2x95
4040	SPOB60	LED-Strahler, 2x	A+	2 x 1,5	4000	2x95
4040	SPOB80	LED-Strahler, 2x	A+	2 x 1,5	4000	2x95
4050	SAN110	LED-Aufbauleuchte Chrom 600 mm	A–A++	3,7	6000	260
4060	SAN60	LED-Aufbauleuchte Chrom 600 mm	A–A++	3,7	6000	260
4060	SPAN60	LED-Aufbauleuchte Chrom 600 mm	A–A++	3,7	6000	260
4060	SAN80	LED-Aufbauleuchte Chrom 600 mm	A–A++	3,7	6000	260
4060	SPAN80	LED-Aufbauleuchte Chrom 600 mm	A–A++	3,7	6000	260
4060	SAN120	LED-Aufbauleuchte Chrom 600 mm	A–A++	3,7	6000	260
4060	SPAN120	LED-Aufbauleuchte Chrom 600 mm	A–A++	3,7	6000	260